

Falco Plasto Crack Filler

Product Description

Falco Plasto Crack Filler is based on elastic copolymer water based product. It is a special filler designed for gap filling up to 2 cm with aggregates (0.1 – 0.3 mm) to give amazing solution for cracks problem which appear on the substrates.

Recommended Usage

To be used for exterior & interior substrate such as concrete, plaster and gypsum board.

Technical Data

Color	White
Finish	Textured / Matt
Solid Content	65% ± 2 by volume
Viscosity	21 - 23 poises @ 25°C.
Specific gravity	1.68 ± 0.1 gm/cm ³
Drying time	2 hours (depending on the cracks)
Cleaning	Fresh water

Application Data

Surface Preparation

The surface must be clean, dry and free from dust, oil, grease and any contaminations.

Tools

Spatula.

Application Method

Apply **Falco Plasto Crack Filler** by spatula for cracks only.

Note: paint System may be varying according to the substrate.

Packing size

- 1 liter, 1 US gallon and 5 US gallons plastic or metallic cans (for local).
- 1 liter, 1 US gallon, 18 liters metallic cans (for export).

Storage

- The product should be stored in a dry, cool place and away from direct sun light.
- Cans should be well closed, classified according to the material's base and to be arranged by a maximum 3 plastic cans/row and 5 metallic cans/row.

WATER BASE

Health and safety

- Inhalation Risks:

Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.

- Skin & Eye Contact:

Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.

- Skin Absorption: None expected.

- Ingestion Health Risks:

It may be harmful or fatal. If swallowed ingestion may cause nausea, vomiting & diarrhea. Consult a physician.

- Health Hazards : Acute & chronic (not expected).

- Emergency & First Aid Procedures:

1. Dermal : Clean with soap & water.
2. Ingestion : Consult a physician.
3. Inhalation : Remove to fresh air.

Fire & Fire Fighting Data

Flash Point : None.
Flammable Limits : None.
Extinguishing Media : Foam, Alcohol Foam, Co2, Dry Chemical or Water.

Physical / Chemical Characteristics

Vapor Density : Heavier than air.
Evaporation Rate : Slower than other.
Solubility in Water : Soluble.
Appearance & Odor : Paste, Mild Odor

For more information please refer to the Material Safety Data Sheet.