

Falco Stucco Heritage Putty

Product Description

Falco Stucco heritage putty is a special kind of water based colored stucco specially designed to provide attractive marble effect decoration finish.

Recommended Usage

To be used for interior surfaces such as plaster, concrete, cement, gypsum board and wooden surfaces, mainly for hotel lobbies, luxury villas, palaces.

Technical Data

Color	Limited color	
Finish	Semi gloss	
Solid Content	48 % ± 2 by volume	
Theoretical spreading rate (m2/kg)	It depends on number of coats applied and on the nature of the surface in general approximate 1 kg/m ² .	
Viscosity	Thick paste	
Specific gravity	1.40 ± 0.05 gm/cm ³	
Drying time	Dry to touch (hours)	1
	Dry to recoat (hours)	6
Thinner / Cleaning	Fresh water	

Hint

Theoretical spreading rate is a value that depends on solid content and desired dry film thickness by the following equation:

$$\text{Theoretical spreading rate} = \frac{10 \times \text{solid content by volume}}{\text{DFT in microns}}$$

Application Data

Surface Preparation

The surface must be clean, dry and free from dust, oil, grease and any contaminations.

Tools

Spatula.

Application Method

Apply three coats of **Falco Stucco Heritage Putty** by spatula thinned with fresh water (10-15% by volume).

WATER BASE

Recommended paint system for interior

- | | |
|-------------------------------|---------|
| • Falco sealer primer (P.V.A) | 1 coat |
| • Falco Stucco Putty | 2 coats |
| • Falco Silk matt | 2 Coats |
| • Falco Stucco Heritage Putty | 3 coats |

Note: paint System may be varying according to the substrate.

Packing size

- 1 liter, 1 US gallon and 5 US gallons plastic or steel cans (for local).
- 1 liter, 1 US gallon, 18 liters steel cans (for export).

Storage

- The product should be stored in a dry, cool place and away from direct sun light.
- Cans should be well closed, classified according to the material's base and to be arranged by a maximum 3 plastic cans/row and 5 steel cans/row.

Health and safety

- Inhalation Risks:

Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.

- Skin & Eye Contact:

Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.

- Skin Absorption : None expected.

- Ingestion Health Risks:

It may be harmful or fatal. If swallowed ingestion may cause nausea, vomiting & diarrhea. Consult a physician.

- Health Hazards : Acute & chronic (not expected).

- Emergency & First Aid Procedures:

1. Dermal : Clean with soap & water.
2. Ingestion : Consult a physician.
3. Inhalation : Remove to fresh air.

Fire & Fire Fighting Data

- | | |
|---------------------|---|
| Flash Point | : None. |
| Flammable Limits | : None. |
| Extinguishing Media | : Foam, Alcohol Foam, Co2, Dry Chemical or Water. |

Physical / Chemical Characteristics

- | | |
|---------------------|----------------------|
| Vapor Density | : Heavier than air. |
| Evaporation Rate | : Slower than other. |
| Solubility in Water | : Soluble. |
| Appearance & Odor | : Paste, Mild Odor |

For more information please refer to the Material Safety Data Sheet.