

Falco Glamorous

Product Description

Falco Glamorous is 100% pure acrylic water based product specially formulated and designed to give a glamorous finish with special effects

Recommended Usage

To be used for all interior surfaces such concrete, plaster and gypsum boards.

Technical Data

Color	White or as per our color card.		
Finish	Smooth / glossy and metallic.		
Solid Content	40% ± 2 by volume		
	Minimum	Maximum	Typical
Wet film thickness (microns)	87.5	112.5	100
Dry film thickness (microns)	35	45	40
Theoretical spreading rate (m2/ltr.)	11	9	10
Viscosity	10 - 15 poises @ 25°C.		
Specific gravity	1.05 ± 0.05 gm/cm³		
Drying time	Dry to touch (hours)	2	
	Dry to recoat (hours)	6	
Thinner / Cleaning	Fresh water		

Hint

Theoretical spreading rate is a value that depends on solid content and desired dry film thickness by the following equation:

$$\text{Theoretical spreading rate} = \frac{10 \times \text{solid content by volume}}{\text{DFT in microns}}$$

Application Data

Surface Preparation

The surface must be clean, dry, and free from dust, oil, grease and any contaminations.

Tools

Roller, spatula or sponge.

Application Method

Apply three coats of **Falco Glamorous** by roller, spatula or sponge thinned with fresh water (10% by volume).

WATER BASE

Recommended paint system for interior

- Falco Sealer Primer (P.V.A) 1 coat
- Falco Stucco Putty 2 coats
- Falco Silk 2 coats
- Apply **Falco Glamorous** depending on desired effect.

Note: paint System may be varying according to the substrate.

Packing size

- 1 liter, 1 US gallon and 5 US gallons plastic or steel cans (for local).
- 1 liter, 1 US gallon, 18 liters steel cans (for export).

Storage

- The product should be stored in a dry, cool place and away from direct sun light.
- Cans should be well closed, classified according to the material's base and to be arranged by a maximum 3 plastic cans/row and 5 steel cans/row.

Health and safety

- Inhalation Risks:
Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.
- Skin & Eye Contact:
Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.
- Skin Absorption: None expected.
- Ingestion Health Risks:
It may be harmful or fatal. If swallowed ingestion may cause nausea, vomiting & diarrhea. Consult a physician.
- Health Hazards : Acute & chronic (not expected).
- Emergency & First Aid Procedures:
 1. Dermal : Clean with soap & water.
 2. Ingestion : Consult a physician.
 3. Inhalation : Remove to fresh air.

Fire & Fire Fighting Data

- Flash Point : None.
- Flammable Limits : None.
- Extinguishing Media : Foam, Alcohol Foam, Co2, Dry Chemical or Water.

Physical / Chemical Characteristics

- Vapor Density : Heavier than air.
- Evaporation Rate : Slower than other.
- Solubility in Water : Soluble.
- Appearance & Odor : Liquid, Mild Odor

For more information please refer to the Material Safety Data Sheet.