

## Falco Non Cracking Tex

### Product Description

**Falco Non Cracking Tex** is based on Styrene Acrylic copolymer medium textured water based product. Specially selected and formulated to provide maximum protection against concrete cracking. It is distinguished by its flexibility and crack-bridging properties. Moisture resistance is applicable.

### Recommended Usage

To be used for exterior & interior concrete, plaster, gypsum and wood works.

### Technical Data

|                                      |                                |         |         |
|--------------------------------------|--------------------------------|---------|---------|
| Color                                | White or as per our color card |         |         |
| Finish                               | Textured / Matt                |         |         |
| Solid Content                        | 58% ± 2 by volume              |         |         |
|                                      | Minimum                        | Maximum | Typical |
| Wet film thickness (microns)         | 603                            | 862     | 733     |
| Dry film thickness (microns)         | 350                            | 500     | 425     |
| Theoretical spreading rate (m2/ltr.) | 1.65                           | 1.2     | 1.4     |
| Viscosity                            | Paste.                         |         |         |
| Specific gravity                     | 1.45 ± 0.05 gm/cm <sup>3</sup> |         |         |
| Drying time                          | Dry to touch (hours)           | 1       |         |
|                                      | Dry to recoat (hours)          | 8       |         |
| Thinner / Cleaning                   | Fresh water                    |         |         |

### Hint

Theoretical spreading rate is a value that depends on solid content and desired dry film thickness by the following equation:

$$\text{Theoretical spreading rate} = \frac{10 \times \text{solid content by volume}}{\text{DFT in microns}}$$

### Application Data

#### Surface Preparation

The surface must be clean, dry and free from dust, oil, grease and any contaminations.

#### Tools

Trowel.

#### Application Method

Apply one or two coats of **Falco Non Cracking Tex** by brush, roller or trowel thinned with fresh water (10 - 15% by volume).

## WATER BASE

---

### Recommended paint system

- Falco Tex Primer 1 coat
- Falco Non Cracking Tex 1 or 2 coats

**Note:** paint System may be varying according to the substrate.

### Packing size

- 1 US gallon and 5 US gallons plastic or steel cans (for local).
- 1 US gallon, 18 liters steel cans (for export).

### Storage

- The product should be stored in a dry, cool place and away from direct sun light.
- Cans should be well closed, classified according to the material's base and to be arranged by a maximum 3 plastic cans/row and 5 steel cans/row.

### Health and safety

- Inhalation Risks:  
Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.
- Skin & Eye Contact:  
Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.
- Skin Absorption : None expected.
- Ingestion Health Risks:  
It may be harmful or fatal. If swallowed ingestion may cause nausea, vomiting & diarrhea. Consult a physician.
- Health Hazards : Acute & chronic (not expected).
- Emergency & First Aid Procedures:
  1. Dermal : Clean with soap & water.
  2. Ingestion : Consult a physician.
  3. Inhalation : Remove to fresh air.

### Fire & Fire Fighting Data

- Flash Point : None.
- Flammable Limits : None.
- Extinguishing Media : Foam, Alcohol Foam, Co2, Dry Chemical or Water.

### Physical / Chemical Characteristics

- Vapor Density : Heavier than air.
- Evaporation Rate : Slower than other.
- Solubility in Water : Soluble.
- Appearance & Odor : Paste, Mild Odor

For more information please refer to the Material Safety Data Sheet.