

Falco Tex I without Marble Chips (WMC)

Product Description

Falco Tex I (WMC) is based on acrylic copolymer heavy textured water based product without marble chips. It is a weather and alkali resistance product.

Recommended Usage

To be used for exterior & interior concrete, plaster, gypsum and wood works.

Technical Data

Color	White or as per our color card		
Finish	Heavy textured / Matt		
Solid Content	60% ± 2 by volume		
	Minimum	Maximum	Typical
Wet film thickness (microns)	250	500	375
Dry film thickness (microns)	660	330	495
Theoretical spreading rate (m ² /ltr.)	1	2	1.33
Viscosity	Paste.		
Specific gravity	1.75 ± 0.05 gm/cm ³		
Drying time	Dry to touch (hours)		1
	Dry to recoat (hours)		8
Thinner / Cleaning	Fresh water		

Hint

Theoretical spreading rate is a value that depends on solid content and desired dry film thickness by the following equation:

$$\text{Theoretical spreading rate} = \frac{10 \times \text{solid content by volume}}{\text{DFT in microns}}$$

Application Data

Surface Preparation

The surface must be clean, dry and free from dust, oil, grease and any contaminations.

Tools

Texture roller.

Application Method

Apply one coat of Falco Tex I (WMC) by brush or roller thinned with fresh water (10 - 15% by volume).

WATER BASE

Recommended paint system

- | | |
|---------------------|--------|
| • Falco Tex Primer | 1 coat |
| • Falco Tex I (WMC) | 1 coat |

Note: paint System may be varying according to the substrate.

Packing size

- 1 US gallon and 5 US gallons plastic or steel cans (for local).
- 1 US gallon, 18 liters steel cans (for export).

Storage

- The product should be stored in a dry, cool place and away from direct sun light.
- Cans should be well closed, classified according to the material's base and to be arranged by a maximum 3 plastic cans/row and 5 steel cans/row.

Health and safety

- Inhalation Risks:
Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.
- Skin & Eye Contact:
Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.
- Skin Absorption : None expected.
- Ingestion Health Risks:

It may be harmful or fatal. If swallowed ingestion may cause nausea, vomiting & diarrhea. Consult a physician.
- Health Hazards : Acute & chronic (not expected).
- Emergency & First Aid Procedures:
 1. Dermal : Clean with soap & water.
 2. Ingestion : Consult a physician.
 3. Inhalation : Remove to fresh air.

Fire & Fire Fighting Data

- | | |
|---------------------|---|
| Flash Point | : None. |
| Flammable Limits | : None. |
| Extinguishing Media | : Foam, Alcohol Foam, Co2, Dry Chemical or Water. |

Physical / Chemical Characteristics

- | | |
|---------------------|------------------------------|
| Vapor Density | : Heavier than air. |
| Evaporation Rate | : Slower than other. |
| Solubility in Water | : Soluble. |
| Appearance & Odor | : Viscous Texture, Mild Odor |

For more information please refer to the Material Safety Data Sheet.