

Falco Texo Plaster

Product Description

Falco Texo Plaster is based on Acrylic copolymer ready to use water base product. It can be applied directly to either new or old solid surfaces, it has perfect adhesion properties, crack bridging ability and the finished surfaces with **Falco Texo Plaster** do not require priming before painting

Recommended Usage

To be used on pre-cast concrete, fair-face, level brick work gypsum board and joint filling subject to the full cure of material for internal & external substrates.

Technical Data

Color	Brown for base coat.	
Finish	Matt / smooth finish.	
Viscosity	Thick paste.	
Specific gravity	1.85 gm/cm ³	
Recommended Film Thickness (DFT).	3 mm Max/coat.	
Drying time	Dry to touch (hours)	3
	Dry to recoat (hours)	4
Thinner / Cleaning	Fresh water	
Volatile Organic Compounds (VOC)	< 1 g/l (as per SCAQMD304-91 DMS 0033:2016)	

Application Data

Surface Preparation

The surface must be clean, dry and free from dust, oil, grease and any contaminations.

Tools

Spatula or scraper.

Application Method

Falco Texo Plaster is ready to use and it could be diluted with 2-3 % water if required. Patch and repair uneven damaged surfaces. Spray the first coat and level with steel edged spatula. it could be applied by spray or hand application.

Any paint system could be apply on **Falco Texo Plaster** and glass fiber mesh between the coats could be use if required.

Packing size

- 25 kgs bag (for local & export).

Storage

- The product should be stored in a dry, cool place and away from direct sun light.

WATER BASE

Health and safety

- Inhalation Risks:

Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.

- Skin & Eye Contact:

Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.

- Skin Absorption: None expected.

- Ingestion Health Risks:

It may be harmful or fatal. If swallowed ingestion may cause nausea, vomiting & diarrhea. Consult a physician.

- Health Hazards : Acute & chronic (not expected).

- Emergency & First Aid Procedures:

1. Dermal : Clean with soap & water.
2. Ingestion : Consult a physician.
3. Inhalation : Remove to fresh air.

Fire & Fire Fighting Data

Flash Point : None.
Flammable Limits : None.
Extinguishing Media : Foam, Alcohol Foam, Co2, Dry Chemical or Water.

Physical / Chemical Characteristics

Vapor Density : Heavier than air.
Evaporation Rate : Slower than other.
Solubility in Water : Soluble.
Appearance & Odor : Paste, Mild Odor

For more information please refer to the Material Safety Data Sheet.