

## Falco Latex Anti-fungus

### Product Description

Falco Latex Anti-fungus is based on Vinyl Acrylic Copolymer water based product. It's washable, easy to apply and smooth finish paint. It contains an additive to give long term protection against deterioration of the dried paint film due to the growth of fungi and algae.

### Recommended Usage

To be used for exterior and interior surfaces such as concrete, plastered wall, above false ceiling and wood surfaces mainly for hospitals, clinics and schools.

### Technical Data

|                                      |                                 |         |         |
|--------------------------------------|---------------------------------|---------|---------|
| Color                                | Black or as per our color card. |         |         |
| Finish                               | Smooth / Matt                   |         |         |
| Solid Content                        | 42% ± 2 by volume               |         |         |
|                                      | Minimum                         | Maximum | Typical |
| Wet film thickness (microns)         | 119                             | 143     | 131     |
| Dry film thickness (microns)         | 50                              | 60      | 55      |
| Theoretical spreading rate (m2/ltr.) | 8.4                             | 7       | 7.6     |
| Viscosity                            | 26 - 28 poises @ 25°C.          |         |         |
| Specific gravity                     | 1.4 ± 0.05 gm/cm³               |         |         |
| Drying time                          | Dry to touch (hours)            | 1       |         |
|                                      | Dry to recoat (hours)           | 2       |         |
| Thinner / Cleaning                   | Fresh water                     |         |         |

### Hint

Theoretical spreading rate is a value that depends on solid content and desired dry film thickness by the following equation:

$$\text{Theoretical spreading rate} = \frac{10 \times \text{solid content by volume}}{\text{DFT in microns}}$$

### Application Data

#### Surface Preparation

The surface must be clean, dry and free from dust, oil, grease and any contaminations.

#### Tools

Brush, roller or spray.

#### Spray Data

Pressure at nozzle : 140-190 kg/cm<sup>2</sup> (2100 PSI)

## WATER BASE

---

|             |                                       |
|-------------|---------------------------------------|
| Nozzle tip  | : 0.021"- 0.027"                      |
| Spray Angle | : 65 – 80°                            |
| Filter      | : be sure that the filters are clean. |

### Application Method

Apply **Falco Latex Anti-fungus** (top coat) by brush or roller thinned with fresh water (10-15% by volume).

### Recommended paint system:

- |                                                            |                |
|------------------------------------------------------------|----------------|
| • Falco Sealer Primer P.V.A or Acrylic Emulsion Primer H.Q | 1 coat         |
| • Falco Stucco Putty                                       | 2 coats        |
| • <b>Falco Latex Anti-fungus</b>                           | <b>2 coats</b> |

### Above false ceiling

- |                                         |                     |
|-----------------------------------------|---------------------|
| • Falco Sealer Primer P.V.A "if needed" | 1 coat              |
| • <b>Falco Latex Anti-fungus</b>        | <b>1 or 2 coats</b> |

**Note:** paint System may be varying according to the substrate.

### **Packing size**

- 1 liter, 1 US gallon and 5 US gallons plastic or steel cans (for local).
- 1 liter, 1 US gallon, 18 liters steel cans (for export).

### **Storage**

- The product should be stored in a dry, cool place and away from direct sun light.
- Cans should be well closed, classified according to the material's base and to be arranged by a maximum 3 plastic cans/row and 5 steel cans/row.

### **Health and safety**

- Inhalation Risks:

Vapor or mist can cause headache, nausea & irritation of the nose throat & lungs.

- Skin & Eye Contact:

Use good personal hygiene practices while working with this material. Dry contaminated clothing before reuse. For eye contact, flush with fresh water for at least 15 minutes. If irritation persists, get medical attention.

- Skin Absorption: None expected.

- Ingestion Health Risks:

It may be harmful or fatal. If swallowed ingestion may cause nausea, vomiting & diarrhea. Consult a physician.

## WATER BASE

---

- Health Hazards : Acute & chronic (not expected).
- Emergency & First Aid Procedures:
  1. Dermal : Clean with soap & water.
  2. Ingestion : Consult a physician.
  3. Inhalation : Remove to fresh air.

### Fire & Fire Fighting Data

Flash Point : None.  
Flammable Limits : None.  
Extinguishing Media : Foam, Alcohol Foam, Co2, Dry Chemical or Water.

### Physical / Chemical Characteristics

Vapor Density : Heavier than air.  
Evaporation Rate : Slower than other.  
Solubility in Water : Soluble.  
Appearance & Odor : Liquid, Mild Odor

For more information please refer to the Material Safety Data Sheet.